



Pakistan Petroleum Limited

11:28 Pakistan Time

Date & Time Of Print: 22/03/2022 11:28:28 - Time Zone: Pakistan Time
Buyer Organisation: Pakistan Petroleum Limited

OVERVIEW

Code	rfq_20955
Title	0010165680 - PD/MEC/PP/20955/22 - SUPPLY OF SPARES FOR INDUSTRIAL ENGINE
Description	ADHI STORE
Status	Running

RFQ SETTINGS

Online Response Required:	Yes
Event Currency	PKR
Allow Bidding Group Response	No
Publication	15/03/2022 16:03:53
Closing	30/03/2022 15:00:00
Time Limit for Expressing Interest	30/03/2022 15:00:00
Awarding Strategy	Best Price

ATTACHMENTS

Path	Description	Folder Size		
root (5)		22,179 KB		
Filename	Downloadable	Last Modification Date	Description	File Size
Guidlines for Visitors.pdf	Yes	03/03/2022		18,958 KB
Instructions, T&Cs for Procurement of Materials.pdf	Yes	03/03/2022		392 KB
Instructions, T&Cs for Procurement of Services.pdf	Yes	03/03/2022		953 KB
Supplier User Guide - Responding to Online Tenders_1.pdf	Yes	03/03/2022		1,220 KB
Supplier User Guide - Using the Messaging Tool_1.pdf	Yes	03/03/2022		658 KB

ENVELOPES

Qualification Envelope	No
Technical Envelope	Yes
Commercial Envelope	Yes

TECHNICAL ENVELOPE

General Attachments
Allowed

TERMS:

Question	Description	Question Type
DELIVERY:	DELIVERY:	Text
BID VALIDITY	BID VALIDITY	Date

QUESTIONS RELATED TO ITEM SPECIFICATIONS:

Question	Description	Question Type
NOTE	Below is the list of required items. Respond if you are quoting for same specs or a variant.	
Question	Description	Question Type

0010165680-99-00010	<p>Material Number: 16-01-41989</p> <p>TRANSMITTER: TYPE: Vibration RANGE: 0 to 1 IPS True RMS or 25.4 mm SUPPLY RATING: 11-30VDC EXD CLASS: ATEX/IECEX/KOSHA Ex d IIC T4 OPERATING TEMPERATURE: -40 TO 100 DEG C APPLICATION: For Nodal Compressor Engines & Compressor</p> <p>TEXT:Output:4-20mA Housing Material & Stud Size: 303 SS housing, ½" NPT stud Connection type: Terminal Block, 2-wire5; (4-20 mA output only) Frequency Response:2Hz to 1500 Hz 3dB Load R= 50(V-11)OHMS Hazardous Area Certification & Certified flameproof : ATEX/IECEX/KOSHA Ex d IIC T4 Gb (explosion proof, includes 8200 conduit elbow) 16-AV4BO-0213X S/N: 9217867</p> <p>MANUFACTURER DETAILS: MFG: METRIX:Model:ST5484E-151-0182-00</p>	Option List
0010162770-99-00010	<p>Material Number: 16-25-653</p> <p>REGULATOR,PRESSURE:Y692,3.5-7" WC SPRING,3/4" NPT,CI BODY,BLANKETING GAS, TEXT:FISHER TYPE 2" Y692 GAS BALNKETING REGULATOR PILOT/REGULATOR BODY MATL: CAST IRON SPRING CASE MATL: WCC STEEL LOWER CASING MATERIAL: WCC STEEL SELF OP SPRING RANGE: 3.5 TO 7.0 IN WC PORT DIAMETER: 3/4 INCH END CONNECTIONS: NPT TRIM MATERIAL: SST DIAPHRAGM MATERIAL: NITRILE DISK MATERIAL: NITRILE NACE: NO MANUFACTURER DETAILS: MFG: EMERSON PROCESS MANAGEMENT ASIA:P/N: FSY692-WE2 MFG: FISHER:P/N: Y692</p>	Option List
0010135099-99-00010	<p>Material Number: 16-25-19007</p> <p>STARTER: TYPE: AIR APPLICATION: H-24GL ENGINE,PLANT-2</p> <p>TEXT:MODEL: H24GL LCR, SERIAL NO: C-15360/1</p> <p>Manufacture of Air Starter :- TDI TURBO TWIN MODEL:- T30-I PART NO:- T312-60017-01R</p>	Option List

COMMERCIAL ENVELOPE

General Attachments
Allowed

TOTAL MATERIAL VALUE WITH SURCHARGES

Code	Description	Last PO No / Date / Item Remarks	Unit of Measurement	Quantity
	FOB /Packing Charges (If any)		LUMP SUM	1
	Freight (if any)		LUMP SUM	1

CONFIRM FOLLOWING AS PROVIDED IN THE BID

Question	Description	Question Type
Delivery Period	Delivery Period	Text
Bid Validity	Bid Validity (180 days)	Date
Delivery Terms	Delivery Terms	Text

Country of Origin	Country of Origin	Text
Port of Shipment	Port of Shipment	Text
Payment Terms	Payment Terms [LC / CAD]	Text

LIST OF MATERIALS

Code	Description	Last PO No / Date / Item Remarks	Unit of Measurement	Quantity
0010165680-99-00010	Material Number: 16-01-41989 TRANSMITTER: TYPE: Vibration RANGE: 0 to 1 IPS True RMS or 25.4 mm SUPPLY RATING: 11-30VDC EXD CLASS: ATEX/IECEX/KOSHA Ex d IIC T4 OPERATING TEMPERATURE: -40 TO 100 DEG C APPLICATION: For Nodal Compressor Engines & Compressor TEXT:Output:4-20mA Housing Material & Stud Size: 303 SS housing, ½" NPT stud Connection type: Terminal Block, 2-wire5; (4-20 mA output only) Frequency Response:2Hz to 1500 Hz 3dB Load R= 50(V-11)OHMS	- 00000 / 00-00-0000	EA	4
0010162770-99-00010	Material Number: 16-25-653 REGULATOR,PRESSURE:Y692,3.5-7" WC SPRING,3/4" NPT, CI BODY,BLANKETING GAS, TEXT:FISHER TYPE 2" Y692 GAS BALNKETING REGULATOR PILOT/REGULATOR BODY MATL: CAST IRON SPRING CASE MATL: WCC STEEL LOWER CASING MATERIAL: WCC STEEL SELF OP SPRING RANGE: 3.5 TO 7.0 IN WC PORT DIAMETER: 3/4 INCH END CONNECTIONS: NPT TRIM MATERIAL: SST DIAPHRAGM MATERIAL: NITRILE DISK MATERIAL: NITRILE NACE: NO MANUFACTURER DETAILS: MFG: EMERSON PROCESS MANAGEMENT ASIA:P/N: FSY692-WE2	4500099223 - 00020 / 04-08-2020	EA	1
0010135099-99-00010	Material Number: 16-25-19007 STARTER: TYPE: AIR APPLICATION: H-24GL ENGINE,PLANT-2 TEXT:MODEL: H24GL LCR, SERIAL NO: C-15360/1 Manufacture of Air Starter :- TDI TURBO TWIN MODEL:- T30-I PART NO:- T312-60017-01R	4500075732 - 00010 / 03-01-2017	EA	1
Sales / Services Tax %	Total (Inclusive Sales Tax)			
Section total included in total?				Yes