

00:22 Pakistan Time

Date & Time Of Print: 11/04/2022 00:22:20 - Time Zone: Pakistan Time Buyer Organisation: Pakistan Petroleum Limited

#### **OVERVIEW**

Code rfq\_21194

Title 0010185836 - PD/MEC/PP/21194/22 - SUPPLY OF

CONSUMABLE ITEMS

Description SFGC STORE Status Running

#### **RFQ SETTINGS**

Online Response Required:

Event Currency

Allow Bidding Group Response

Yes

PKR

No

 Publication
 30/03/2022 11:24:15

 Closing
 18/04/2022 11:00:00

 Time Limit for Expressing Interest
 18/04/2022 11:00:00

Awarding Strategy Best Price

#### **ATTACHMENTS**

Path		Description	Folder Size	
root (5)			21,889 KB	
Filename	Downloadable	Last Modification Date	Description	File Size
Guidlines for Visitors.pdf	Yes	26/03/2022		18,958 KB
Instructions TCs For Procurement Of Materials.pdf	Yes	26/03/2022		393 KB
Instructions TCs For Procurement Of Services.pdf	Yes	26/03/2022		662 KB
Supplier User Guide - Responding to Online Tenders_1.pdf	Yes	26/03/2022		1,220 KB
Supplier User Guide - Using the Messaging Tool_1.pdf	Yes	26/03/2022		658 KB

# **ENVELOPES**

Qualification EnvelopeNoTechnical EnvelopeYesCommercial EnvelopeYes

# **TECHNICAL ENVELOPE**

General Attachments Allowed

### **QUESTIONS RELATED TO ITEM SPECIFICATIONS:**

Question Description

NOTE Below is the list of required items. Respond if you are quoting for same specs or a variant.

Question Description Question Type

CLEANER:

TYPE: ANTIRUST, WD-40 FORM: LIQUID SPRAY TYPE CONTAINER: 330 ML TIN

APPLICATION: USE FOR MULTI PURPOSE

TEXT:Other Technical specifications

Appearance: Aerosol - Aerosolized Liquid Bulk - Liquid

Color Light amber cloudy liquid

Odor Characteristic

Freeze Point/Pour Point <(><<)>-81° F (-63° C) (ASTM D-97)

Kinematic Viscosity @ 100° F (38° C): 2.8 CST

Specific Gravity @ 77° F (25° C): 0.81 Boiling Point (initial): 360° F (183° C) Flash Point: 138° F (59° C)(TCC)

#### Mandatory Requirement

a) Supply shall be made from latest production batch.

b) MSDS shall be provided before / along / after

delivery of consignment.

c) Production and expiry dates of material shall be printed separately

on each Tin.

MANUFACTURER DETAILS: MFG: UNKNOWN:P/N: WD-40

0010185836-99-00020Material Number: 13-01-505

ADHESIVE:

TYPE: PERMATEX RED RTV SILICONE CONTAINER: 250 GRAM TUBE GRADE: HIGH TEMPERATURE

APPLICATION: SEALING & GASKET MAKING

TEXT:Item is Proprietary hence it is to be directly procured only from PERMATEX or their authorized distributors.

Following documents must be submitted along with the quotation.

- Supplier must show valid OEM authorized agent certificate.
- Supplier to submit OEM certificate of conformity.
- Bill of Landing or Bill of Entry.
- Certificate of Analysis stating product detail, batch number and properties.

Agent of PERMATEX is (ADENWALA & SONS) OR EQUIVALENT.

MANUFACTURER DETAILS: MFG: PERMATEX:P/N: 81409

0010185836-99-00030 Material Number: 13-08-9578

PAD, CLEANING:

TYPE: Scotch Brite Without Sponge

SIZE: Heavy Duty

MATERIAL: Washing up pad

APPLICATION: Scotch Brite Heavy Duty Washing up pad

TEXT:Scotch-Brite® Heavy Duty Scour Pad

Must be Without Sponge

Brand:Scotch-Brite™

Cleaning Strength: Heavy Duty

Colour:Green

Package Contents: 4, 4 Pack Product Type:Scour Pad

Product Usage : BBQ's, General Cleaning

Recommended Surfaces: Cast Iron, Pots & Pans, Rubber

Type of Cleaning:Scour, Scrub

**Option List** 

Option List

0010185836-99-00060 Material Number: 13-08-129

GLOVES:

TYPE: Safety Gloves PVC Dotted

SIZE: Fit all

MATERIAL: Cotton knitted (woven fabric)

COLOR: Grey

PALM/BACK: Single (palm) side PVC dotted

APPLICATION: General material handling works such as pipes etc.

TEXT: Fitting: Comfortable and tight grip

Others: Washable, Weight 600 grams

0010185836-99-00070 Material Number: 13-01-665

ABRASIVE, SHEET: TYPE: SANDING WIDTH: 4" LENGTH: 12" SIZE: 4 X 12 GRIT: 00FINE MATERIAL: EMERY

BOND/BACKING: CLOTH BACKING

TEXT:Raisan bond electro coted best quality

0010185836-99-00090 Material Number: 13-01-669

ABRASIVE: TYPE: SANDING

SIZE: 230MM X 280MM (9" X 11")

GRIT: #3

MATERIAL: ALUM OXIDE

BOND/BACKING: CLOTH BACKING

TEXT:PAPER

0010185836-99-00100 Material Number: 13-01-199

BRUSH, WIRE:

TEXT:BRUSH WIRE STAINLESS STEEL MAKE: CHINA 4 ROW

0010185836-99-00110 Material Number: 21-01-573

CLEANER: TYPE: CHEMICAL FORM: LIQUID

APPLICATION: TURBINE PARTS CLEANING

MANUFACTURER DETAILS: MFG: BIOMEX INDUSTRY:\*

0010185836-99-00120 Material Number: 27-99-420

MATERIAL: TYPE: GASKET COMPOSITION: CAF

SIZE: 1.5 M WD X 2 M LG X 1.5MM THK SHEET

PRESSURE RATING: 150 LB TEMPERATURE RATING: 150 DEG C

TEXT:PARENT EQUIPMENT DETAILS: GENERAL PURPOSE CONSUMABLE Option List

**Option List** 

Option List

Option List

Option List

**Option List** 

0010185836-99-00130 Material Number: 27-99-421

MATERIAL:

TYPE: GASKET SHEET

COMPOSITION: Compressed Non-Aesbostos Fibre / Graphite

SIZE: 1.5 M WD X 2 M LG X 1MM THK SHEET

PRESSURE RATING: 150 LB ABOVE

TEMPERATURE RATING: 150 DEG C ABOVE APPLICATION: GENERAL PURPOSE CONSUMABLE

0010185836-99-00140 Material Number: 13-01-044

MATERIAL:

TYPE: JOINT

COMPOSITION: KLINGERITE SIZE: 60" X 80" X 0.5MM SHEET

TEXT:PACKING KLINGERITE Sheet, STANDARD SHEET SIZE: 60"X80"X0.5mm

0010185836-99-00150Material Number: 13-01-042

GASKET COMPRESSED 1/8"(THICK) x 60" x 60"(3.1MM) ASBESTOS

SHEET SIZE

0010185836-99-00160 Material Number: 12-18-225

COMPOUND, SEALING:

TEXT:LOCTITE-495
MANUFACTURER DETAILS:
MFG: LOCTITE:P/N:

0010185836-99-00170 Material Number: 13-01-004

RAG:

TYPE: COTTON SIZE: 10"x10" MATERIAL: COTTON COLOR: MIXED

TEXT: RAG COTTON 10"x10" COLORED NEWHOSIERY CLOTH

0010185836-99-00180 Material Number: 13-01-048

DYE:

COLOR: PRUSSAIN BLUE (MARKING BLUE), ENGINEER'S BLUE

0010185836-99-00190 Material Number: 18-01-292

TIE,CABLE: WIDTH: 2.8MM LENGTH: 190MM STRENGTH: 40 LB MATERIAL: NYLON COLOR: WHITE/BLACK

TEXT:TENSILE STRENGTH: 80 N, OPERATING TEMP. -40 TO 85 DEG C,FLAME RESISTANT, CSA

CERTIFIED, ROHS COMPLIANT MANUFACTURER DETAILS: MFG: UNKNOWN:P/N: T30L-L 190

0010185836-99-00200 Material Number: 18-02-881

CLEANER:

TYPE: CO CONTACT FORM: GREEN AEROSOL

CONTAINER: 400 ML SPRAY CAN

TEXT:CO-CONTACT, NON-DESTRECTIVE EXAMINATION, ELECTRIC CONTACT,

MAINTENANCE AEROSEL MANUFACTURER DETAILS: MFG: UNKNOWN:P/N: 7437K12 Option List

Option List

Option List

**Option List** 

Option List

Option List

**Option List** 

Option List

0010185836-99-00210 Material Number: 36-08-307

TAPE:

TYPE: MASKING

SIZE: 2" Inch Width x 18 MM Thickness x 72 M Length

MATERIAL: ADHESIVE BACKED PAPER

COLOR: WHITE

0010185836-99-00220 Material Number: 33-07-41979

GREASE, INDUSTRIAL:

TYPE: MOLYKOTE 55 O-RING GREASE VALVE LUBRICANT

TEMPERATURE RATING: -65 to 175 Degree C

COLOR: OFF WHITE

APPLICATION: CONTROL VALVE ACTUATOR

TEXT:Name: MOLYKOTE® 55 O-Ring Grease

Product type: Grease Chemistry: Silicon Color: Off-white

NLGI consistency class: approx. 2

ASTM D 217 Worked Penetration: mm/10 290 ISO 2811 Density at 20°C (68°F): g/cm^3 0.98

DIN 51 562 Base oil viscosity at 25°C (77°F): mm2 /s 100 Service temperature:  $^{\circ}$ C -65 TO +175/ $^{\circ}$ F -85 TO +347 ASTM D 566 Drop point:  $^{\circ}$ C 220/ $^{\circ}$ F 428

ASTM D147880 Low temperature torque test at -65°C (-85°F)

Initial break-away torque: Nm 325x10-3

Torque after 20 minutes running time: Nm 35x10-3

Coefficient of friction

Steel ball against plastic surface (POM) Ø ball = 12.7mm, load = 6.3N, v = 10 mm/s,

24h:  $\mu$ = 0.03 Resistance

DIN 51 808 Oxidation resistance, pressure drop 100h,

99°C (210°F): 0.1 Bar Corrosion protection

DIN 51 802 SKF-Emcor method - degree of corrosion: 0

FED Std 791 Bleed, 24h at 150°C (302°F): 3.0% Evaporation, 24h at 150°C (302°F): 1.4% ASTM D 1264 Water washout resistance: 4.2%

MFG: DOW CORNING / Equivalent

APPLICATION: For lubrication of Flowserve control valve

MANUFACTURER DETAILS:

MFG: DOW CORNING:MOLYKOTE 55 O-RING GREASE

0010185836-99-00230 Material Number: 16-01-42220

SFALER:

TYPE: Part # Loctite 2422 APPLICATION: Loctite 2422

TEXT: Apply Loctite 2422 to the contact surfaces of exhaust valve seat bores.

MANUFACTURER DETAILS:

MFG: WAUKESHA GAS ENGINE:L7044 GSI, L5794 GSI, P9394 GSI

MFG: WAUKESHA GAS ENGINE:Loctite 2422

MFG: WAUKESHA GAS ENGINE:5283704311, 5283704860, C-15113/3

## **MANDATORY REQUIREMENTS**

Question Description

CURRENCY PRICE MUST BE QUOTED IN PKR AND FOR BASIS ONLY.

DELIVERY PLEASE SUBMIT YOUR QUOTE ON FOR BASIS PREFERABLY IN PKR FOR FREE DELIVERY OF MATRIAL AT OUR Yes/No WEST WHARF STORES, KARACHI.

Option List

**Option List** 

Option List

Question Type Yes/No

Value

Value

Question	Description	Question Type
Submission of Bid	It is mandatory for the bidders to submit online bids through PPL e-Procurement portal as per attached user's Guide/ Manual.  if Disclaimer: PPL shall not have or accept any liability, obligation or responsibility in the event that a bid is rejected for failure on the part of the bidder to submit an online bid through our PPL e-Procurement portal, as stated above.	Text
Review of all attachments	By accepting all attached documents it shall be considered that you have read and reviewed complete attachments (documents) thoroughly and accept our all terms & conditions, which are available in "Attachments => Visible to Suppliers"	Yes/No Value
Technical Literature/ Brochures	Please provide Technical Literature/ Brochures/ supporting documents alongwith technical bid	Attachment
Understanding and Compliance	Supplier to confirm complete understanding and compliance of the Specification being asked for material	Yes/No Value
MTC	Supplier to submit all relevant certificates including MTCs at the time of delivery.	Yes/No Value
Performance Guarantee (PG)	The Seller is required to provide at his own cost, a Performance Guarantee (text draft will be provided with purchase order) in the form of a Bank Guarantee issued by a PPL's approved bank equivalent to 10% of the total CFR Value of the Purchase Order, within ten(10) days of receipt of the Purchase Order (PO).  The Seller shall extend the validity of the Bid Bond accordingly as required till submission of Performance Guarantee. This will serve to guarantee that the material is delivered as per schedule of requirement and the performance of the equipment ordered. The Performance Guarantee must remain valid for at least 18 months after the date of last shipment or 12 months after the commissioning of the equipment whichever is earlier. If Seller is unable to meet its obligations as per the tender / RFQ / Purchase Order, the Performance Guarantee may be required to be extended or otherwise encashed as per Company's discretion."	Yes/No Value
Liquidated Damages (LD)	The vendor shall be liable to pay the Company Liquidated Damages(LD) If delivery is effected beyond the delivery date referred in Purchase Order, value of invoice will automatically stand reduced at the rate of 1% of the original value per week to a maximum of 5% for the delayed period.	Yes/No Value
Partial/ Split orders	PPL reserves the right to award a partial / split order, quotation. The bidder should clearly specify if this condition is not acceptable. Otherwise, we will presume that partial/split order is acceptable to the bidder.	Yes/No Value
Order acknowledgment	In case of Purchase order if awarded, vendor must submit order acknowledgment on beneficiary's letterhead within seven (07) days of receipt of Purchase Order, failing which Company reserves the right to consider order cancellation without any liability	Yes/No Value
Exception/ Deviation List	Exception list is to be attached with Commercial and Technical Bid/proposal, if any.	Attachment
Un-Priced copy of Bid Bond	Please attached Un-Priced copy of Bid Bond, if value over Rs. 02 Million	Attachment
Manufacturer's name	Please mention Manufacturer's name/ OEM / Beneficiary's name	Text

#### **COMMERCIAL ENVELOPE**

General Attachments Allowed

# LIST OF MATERIALS

Code Description
0010185836-99-00010Material Number: 13-50-011

CLEANER: TYPE: ANTIRUST , WD-40 FORM: LIQUID SPRAY TYPE CONTAINER: 330 ML TIN

APPLICATION: USE FOR MULTI PURPOSE

TEXT:Other Technical specifications

Appearance: Aerosol - Aerosolized Liquid Bulk - Liquid

Color Light amber cloudy liquid

Odor Characteristic

Freeze Point/Pour Point  $<(><<)>-81^{\circ} F (-63^{\circ} C)$  (ASTM

D-97)

Kinematic Viscosity @ 100° F (38° C): 2.8 CST

Specific Gravity @ 77° F (25° C): 0.81

Boiling

Last PO No / Date / Unit of Item Remarks Measurement 4500107107 - TIN 504 00030 / 08-03-2022

0010185836-99-00020 Material Number: 13-01-505 4500106375 -EΑ 70 ADHESIVE: 00020 / TYPE: PERMATEX RED RTV SILICONE 17-02-2022 **CONTAINER: 250 GRAM TUBE GRADE: HIGH TEMPERATURE** APPLICATION: SEALING & GASKET MAKING TEXT: Item is Proprietary hence it is to be directly procured only from PERMATEX or their authorized distributors. Following documents must be submitted along with the quotation. • Supplier must show valid OEM authorized agent certificate. • Supplier to submit OEM certificate of conformity. • Bill of Landing or 0010185836-99-00030 Material Number: 13-08-9578 4500106777 -EΑ 560 PAD, CLEANING: 00120 / TYPE: Scotch Brite Without Sponge 03-03-2022 SIZE: Heavy Duty MATERIAL: Washing up pad APPLICATION: Scotch Brite Heavy Duty Washing up pad TEXT:Scotch-Brite® Heavy Duty Scour Pad Must be Without Sponge Brand:Scotch-Brite™ Cleaning Strength: Heavy Duty Colour: Green Package Contents: 4, 4 Pack Product Type:Scour Pad Product Usage: BBQ's, General Cleaning Recommended Surfaces: Cast Iron, Pots & Pans, Rubber Type of Cleaning:Sc 0010185836-99-00060 Material Number: 13-08-129 4500076039 -**PAIR** 1,400 00010 / GLOVES: TYPE: Safety Gloves PVC Dotted 03-03-2022 SIZE: Fit all MATERIAL: Cotton knitted (woven fabric) COLOR: Grey PALM/BACK: Single (palm) side PVC dotted APPLICATION: General material handling works such as pipes etc. TEXT:Fitting: Comfortable and tight grip Others: Washable, Weight 600 grams 0010185836-99-00070 Material Number: 13-01-665 4500098445 -SHT 490 ABRASIVE, SHEET: 00020 / TYPE: SANDING 14-06-2020 WIDTH: 4' LENGTH: 12" SIZE: 4 X 12 **GRIT: 00FINE** MATERIAL: EMERY BOND/BACKING: CLOTH BACKING TEXT:Raisan bond electro coted best quality 0010185836-99-00090 Material Number: 13-01-669 4500107184 -SHT 490 ABRASIVE: 00110 / TYPE: SANDING 22-02-2022 SIZE: 230MM X 280MM (9" X 11") **GRIT: #3** MATERIAL: ALUM OXIDE BOND/BACKING: CLOTH BACKING TEXT:PAPER

0010185836-99-0010	0 Material Number: 13-01-199 BRUSH,WIRE:	4500082021 - 00010 / 03-03-2022	EA	70
	TEXT:BRUSH WIRE STAINLESS STEEL MAKE: CHINA 4 ROW	03 03 2022		
0010185836-99-0011	0 Material Number: 21–01–573 CLEANER: TYPE: CHEMICAL FORM: LIQUID APPLICATION: TURBINE PARTS CLEANING MANUFACTURER DETAILS:	4500105622 - 00010 / 16-11-2021	l	350
	MFG: BIOMEX INDUSTRY:*			
0010185836-99-0012	0 Material Number: 27–99–420 MATERIAL: TYPE: GASKET COMPOSITION: CAF SIZE: 1.5 M WD X 2 M LG X 1.5MM THK SHEET PRESSURE RATING: 150 LB TEMPERATURE RATING: 150 DEG C TEXT:PARENT EQUIPMENT DETAILS:	4500105617 - 00010 / 16-11-2021	EA	21
	GENERAL PURPOSE CONSUMABLE			
0010185836-99-0013	OMaterial Number: 27-99-421  MATERIAL: TYPE: GASKET SHEET COMPOSITION: Compressed Non-Aesbostos Fibre / Graphir SIZE: 1.5 M WD X 2 M LG X 1MM THK SHEET PRESSURE RATING: 150 LB ABOVE TEMPERATURE RATING: 150 DEG C ABOVE APPLICATION: GENERAL PURPOSE CONSUMABLE	4500105617 - 00020 / 16-11-2021 te	EA	21
0010185836-99-0014	0 Material Number: 13-01-044 MATERIAL: TYPE: JOINT COMPOSITION: KLINGERITE SIZE: 60" X 80" X 0.5 MM SHEET  TEXT:PACKING KLINGERITE Sheet, STANDARD SHEET SIZE:	4500102233 - 00060 / 01-03-2021	ft2	350
	60"X80"X0.5mm			
0010185836-99-0015	0Material Number: 13-01-042 GASKET COMPRESSED 1/8"(THICK) x 60" x 60"(3.1MM) ASBESTOS SHEET SIZE	4500105973 - 00080 / 29-12-2021	ft2	350
0010185836-99-0016	0 Material Number: 12–18–225 COMPOUND,SEALING: TEXT:LOCTITE–495 MANUFACTURER DETAILS: MFG: LOCTITE:P/N:	4500104898 - 00020 / 09-11-2021	ТВЕ	14
0010185836-99-0017	0 Material Number: 13-01-004 RAG: TYPE: COTTON SIZE: 10"x10" MATERIAL: COTTON COLOR: MIXED	4500106569 - 00010 / 12-03-2022	kg	2,100

TEXT:RAG COTTON 10"x10" COLORED NEWHOSIERY CLOTH

0010185836-99-00186	OMaterial Number: 13-01-048 DYE: COLOR: PRUSSAIN BLUE (MARKING BLUE), ENGINEER'S BLUE	4500101989 - 00040 / 13-02-2021	EA	14
0010185836-99-00190	OMaterial Number: 18-01-292 TIE,CABLE: WIDTH: 2.8MM LENGTH: 190MM STRENGTH: 40 LB MATERIAL: NYLON COLOR: WHITE/BLACK  TEXT:TENSILE STRENGTH: 80 N, OPERATING TEMP40 TO 85 DEG C,FLAME RESISTANT, CSA CERTIFIED, ROHS COMPLIANT MANUFACTURER DETAILS:	4500105082 - 00050 / 16-09-2021	EA	560
	MFG: UNKNOWN:P/N: T30L-L 190			
0010185836-99-00200	OMaterial Number: 18-02-881 CLEANER: TYPE: CO CONTACT FORM: GREEN AEROSOL CONTAINER: 400 ML SPRAY CAN	4500094702 - 00040 / 09-11-2019	EA	56
	TEXT:CO-CONTACT, NON-DESTRECTIVE EXAMINATION, ELECTRIC CONTACT, MAINTENANCE AEROSEL MANUFACTURER DETAILS: MFG: UNKNOWN:P/N: 7437K12			
0010185836-99-00210	OMaterial Number: 36-08-307 TAPE: TYPE: MASKING SIZE: 2" Inch Width x 18 MM Thickness x 72 M Length MATERIAL: ADHESIVE BACKED PAPER COLOR: WHITE	4500106922 - 00030 / 14-03-2022	EA	280
	OMaterial Number: 33-07-41979 GREASE,INDUSTRIAL: TYPE: MOLYKOTE 55 O-RING GREASE VALVE LUBRICANT TEMPERATURE RATING: -65 to 175 Degree C COLOR: OFF WHITE APPLICATION: CONTROL VALVE ACTUATOR	4500102432 - 00010 / 27-08-2021	gm	28
0010185836-99-00230	TEXT:Name: MOLYKOTE® 55 O-Ring Grease Product type: Grease Chemistry: Silicon Color: Off-white NLGI consistency class: approx. 2 ASTM D 217 Worked Penetration: mm/10 290 ISO 2811 Density at 20°C (68°F): g/cm^3 0.98 DIN 51 562 Base oil viscosity at 25°C (77°F): mm2 /s 100 0 Material Number: 16-01-42220 SEALER: TYPE: Part # Loctite 2422 APPLICATION: Loctite 2422	- 00000 / 00-00-0000	EA	14
	TEXT:Apply Loctite 2422 to the contact surfaces of exhaust valve seat bores.  MANUFACTURER DETAILS: MFG: WAUKESHA GAS ENGINE:L7044 GSI, L5794 GSI, P9394 GSI MFG: WAUKESHA GAS ENGINE:Loctite 2422 MFG: WAUKESHA GAS ENGINE:5283704311, 5283704860, C-15113/3			

Sales / Services Tax % Total (Inclusive Sales Tax) Section total included in total?

#### **CONFIRM FOLLOWING AS PROVIDED IN THE BID**

		Question
Question	Description	Type
Payment	Payment Terms Net 30 day	Text
Terms		
Delivery Period	Delivery Period	Text
Bid Validity	Bid Validity Minimum 90 Days	Date
Delivery/	Delivery Terms	Text
Inctoterm Terms		
Country of	Country of Origin	Text
Origin	country of origin.	
Quoted rates	The rates submitted by bidder shall be firm and final & no change in quoted rates or escalation will be acceptable during the validity and entire contract period. Rates must be inclusive of all applicable taxes, out of pocket cost and other associated costs with all respects except applicable Provisional Services (SST) / Federal Taxes (GST), which need to be appeared as a separate break-up by mentioning relevant applicable tax percentage. Rates should be quoted accordingly as per given format and scope of work, no other hidden/additional cost will be charged/billed	•
Partial/ Spli orders	t PPL reserves the right to award Purchase Order/ contract on technically acceptable & commercially evaluated vendor on overall lowest or itemize basis. The bidder should clearly specify if this condition is	Attachment
	not acceptable. Otherwise, we will presume that partial/split order is acceptable to the bidder.	
Copy of Bid Bond	Please attached copy of Bid Bond, if value over Rs. 02 Million	Attachment
Evaluation of Bids	All bids shall be evaluated in accordance with the evaluation criteria/ Specifications and other terms and conditions of the attached ITB.	l Text

### Commercial Evaluation

-----

The Work Contract / Purchase Order will be awarded to the lowest evaluated bidder declared on the basis of quoted rates on net cost basis i.e. exclusive of any cost recoverable to the Company.